

19



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) Publication number:

**0 335 467 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 16.06.93 (51) Int. Cl.<sup>5</sup>: **A43B 3/00**

(21) Application number: 89200784.0

(22) Date of filing: 28.03.89

(54) Footwear.

(30) Priority: 30.03.88 NL 8800816

(43) Date of publication of application:  
04.10.89 Bulletin 89/40

(45) Publication of the grant of the patent:  
16.06.93 Bulletin 93/24

(64) Designated Contracting States:  
AT BE CH DE ES FR GB GR IT LI LU NL SE

(56) References cited:  
EP-A- 0 121 026  
GB-A- 2 121 219  
NL-A- 8 005 050  
US-A- 3 893 247  
US-A- 4 020 572

(73) Proprietor: INTERMEDIUM B.V.  
Saturnusstraat 30  
NL-2132 HB Hoofddorp(NL)

(72) Inventor: Helster, Aloisius Henricus Maria  
Lasondersingel 109  
NL-7514 BN Enschede(NL)  
Inventor: Nijssen, Andreas Jacobus Louis  
Bisschopstraat 24  
NL-7595 AT Weerselo(NL)

(74) Representative: Schumann, Bernard Herman  
Johan et al  
OCTROOIBUREAU ARNOLD & SIEDSMA  
Sweelinckplein 1  
NL-2517 GK The Hague (NL)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

**EP 0 335 467 B1**

## Description

The invention relates to footwear, comprising:  
electrically energizable signal means adapted  
to produce light, and a source of electric energy for  
powering said signal means,

control means connected between said source  
and said signal means for controlling the ener-  
gization of said signal means,

said signal means comprising a plurality of  
lamps, such as LEDs, arranged in a selected pat-  
tern.

Such footwear is known from EP-A-0 121 026.  
This prior art footwear comprises at least one LED  
that can, by means of a switch, selectively be  
connected and disconnected to and from a battery.

It is a purpose of the invention to make the  
signalling by the footwear for third persons as clear  
as possible.

Thereto the footwear according to the invention  
is characterized in that said lamps are adapted to  
produce light of different colours, and said control  
means are adapted for successively, individually or  
group-wise, energizing said lamps.

Also the footwear may be designed such that  
the signal means are adapted to produce sound. In  
this case e.g. use may be made of varying inten-  
sity and pitch, if desired intermittent.

In order to use the available space as effi-  
ciently as possible that embodiment may serve, in  
which the control means comprise an electronic  
assembly embedded in the sole of the footwear. In  
order to load the energy source as little as possible  
that embodiment is preferred, in which the control  
means comprise an on/off switch.

In this last case e.g. use may be made of a  
pressure sensitive switch arranged in the sole of  
the footwear.

A very simple embodiment is that in which the  
source for electrical energy comprise a battery.  
Also, or if desired in combination therewith, an  
embodiment may serve, in which the source for  
electrical energy comprises a solar cell.

A solar cell can during the use by daylight  
serve for charging a rechargeable battery.

Also use may be made of a separate assembly  
to be fixed to footwear and provided with elec-  
trically energizable signal means and a source for  
electrical energy for energizing these signal means.  
Such an assembly is provided with fixing means for  
fixing to the footwear and may serve for assem-  
bling the footwear herein described before accord-  
ing to the invention.

The invention will now be explained with refer-  
ence to the accompanying drawing of a number of  
embodiments. In the drawing:

Figure 1 is an exploded view of a sport shoe  
according to the invention;

Figure 2 is a perspective view of the shoe  
according to figure 1;

Figure 3 is the section III/III according to figure  
1;

Figure 4 is a view of an alternative embodiment  
corresponding with figure 2;

Figure 5 is a limited exploded view of some  
parts in the same view as figure 1; and

Figure 6 a block-schematic diagram of the elec-  
tric parts of the embodiments according to fig-  
ures 4 and 5.

Figures 1 and 2 show a sport shoe 1. This  
shoe comprises a sole 2, a resilient intermediate  
layer 3, a more or less tray-shaped heel-part 4 and  
a textile envelope 5. The envelope 5 carries a  
loudspeaker 7 covered by a hood 6, said loud-  
speaker 7 by means of wires 8 being connected  
with a printed circuit board 9 fixed in the tray-  
shaped heel part 4.

As appears from figure 3 the heel-part 4 is at  
its lower side provided of four recessed parts 10, in  
which button-shapes batteries can be received.  
Through a through-hole 11 these batteries may be  
connected with the electronic circuit arranged on  
the printed circuit board 9.

The heel-part 4 also comprises, in its vertical  
wall 12, nine through-holes 13 for receiving LEDs.  
These LEDs are alternately coloured red and  
green. The red-coloured LEDs are for the sake of  
convenience all indicated with 14, whilst the green  
LEDs are indicated with 15.

In the resilient layer 3 an air reservoir 16 is  
arranged, which connects by means of a pressure  
conduit 17 with a pressure sensitive switch 18. The  
external connections 19, 20 of this pressure sen-  
sitive switch 18 are in the assembled condition of  
the shoe 1 connected with the printed circuit board  
9 by means of pointed conductors 21, 22 stuck  
into the layer 3.

Four batteries 23 received in the recesses 10  
serve for powering of the electronic circuit 24 car-  
ried by the printed circuit board 9.

When a wearer of the shoe 1 pushes with his  
weight on the resilient layer 3, as a result of the  
compression of the air present in the air reservoir  
16 switch 18 will be closed. Through the connec-  
tions 19, 20 and the pointed conductors 21, 22 by  
means of the batteries 23 energization of the circuit  
24 takes place. As a result hereof the loudspeaker  
7 can produce an amplified sound generated by an  
oscillator, giving a constant, or, if desired, varying  
pitch, a mixture of different tones and/or intermit-  
tent sound. Also LEDs 14, 15 can be caused to  
emit light by operation of the circuit 24, as will be  
hereinafter described with reference to figure 6.

Figure 4 shows a shoe 25 having a compart-  
ment 26 for receiving an elongat battery 27. This  
compartment 26 can be closed by means of a

zipper 28. In this embodiment the loudspeaker 7 is missing, but exclusively use is made of LEDs 14, 15.

Figure 5 shows a resilient layer 29 of an alternative embodiment. This resilient layer exhibits a recess 30 for receiving two elongate batteries 31. At the end of the more or less half-cylindrical recess 30 resilient conduction plates 32, 33 are arranged, which are connected to terminals 19, 20 by means of the wires 34, 35 embedded in layer 29.

The heel-part 36 in the embodiment according to figure 5 is different from the heel-part 4 according to figures 1, 2 and 3, as the recesses 10 are missing and an hand-operated on/off-switch 37 is present, which is arranged in the vertical wall 12 of the heel-part 36.

Figure 6 shows a block-schematic diagram of the circuit used in the embodiments according to figures 4 and 5. Through the wires 34, 35 the two elongate batteries 31 can supply current to a control assembly drawn as a turning switch 38, with which the first terminals of LEDs 14, 15 are connected, whilst the second terminals thereof are connected with batteries 31 through wire 35.

As soon as a trigger unit 39 receives current from batteries 31 as a result of the closing of the switch 37, a first mono-stable multivibrator 40 is energized, which in this temporary energizing condition closes a second switch 41, in such a way that during a time interval determined by multivibrator 40 the switch 41 remains in its closed condition, so that through turning switch 38 LEDs 14, 15 can receive current. Trigger unit 39 also controls a second mono-stable multivibrator 42 having an active period such that controlled by turning switch 38 the multivibrator 42 controls this turning switch 38 during exactly one full cycle of the movable contact 43. In the condition shown the movable contact is in its rest position. As soon as the second multivibrator 42 controls switch 38 the movable contact 43 moves with a previously determined speed in the direction indicated with an arrow 44 along the nine contacts connected with the LEDs 14, 15 in the manner shown in figure 6. If consequently for the sake of convenience the LEDs are referred to with 1, 2, 3, 4, 5, 6, 7, 8, 9 from the lower one to the upper one, then the order in which the LEDs are energized is: 5, 6, 4, 7, 3, 8, 2, 9, 1. After this full cycle, dependent upon the adjustment of the mono-stable multivibrator 42, either the cycle is stopped, or one additional full cycle may be performed. From the rear side a spectator then sees a flickering bright light moving towards the sides of the shoe, the light having the following successive colours: red, green, green, red, red, green, green, red, red.

It will be clear that many other configurations are possible within the framework of the invention. It should be noted that in case of shoes in which Velcro is used as fastening, this Velcro can also comprise switch means or control such means, as a result of which only in case of fastened Velcro the circuit is activated.

The assembly 38 is an active switching assembly, that may comprise integrated circuits.

#### Claims

1. Footwear (1), comprising:
  - electrically energizable signal means (14, 15) adapted to produce light, and source (23) of electric energy for powering said signal means (14, 15),
  - control means (16, 18, 24) connected between said source (23) and said signal means (14, 15) for controlling the energization of said signal means (14, 15),
  - said signal means (14, 15) comprising a plurality of lamps, such as LEDs, arranged in a selected pattern,
  - characterized in that
  - said lamps (14, 15) are adapted to produce light of different colours, and
  - said control means (16, 18, 24) are adapted for successively, individually or group-wise, energizing said lamps.
2. Footwear according to claim 1, characterized in that the signal means (7) are adapted to produce sound.
3. Footwear according to claim 1, characterized in that the lamps (14, 15) are arranged at the rear end of the footwear.
4. Footwear according to claim 1, characterized in that the control means (16, 18, 24) comprise an electronic assembly (24) embedded in the sole of the footwear.
5. Footwear according to claim 1, characterized in that the control means (16, 18, 24) comprise an on/off-switch (18).
6. Footwear according to claim 5, characterized by a pressure sensitive switch (18) arranged in the sole (2) of the footwear (1).

#### Patentansprüche

1. Schuhwerk (1) mit:
  - elektrisch betreibbaren Signalisierungseinrichtungen (14, 15), die zur Erzeugung von Licht ausgebildet sind, und einer elektrischen





